

Hallmark Doors & Panels Itd



GLAZED OUAL CERTIFIED FD30 COMPOSITE FIRE DOORS FIRE & SECURITY REGISTANT DOOR SETS



Independent 3rd party accreditation / audit. Laminated glass on pyrobelite.



WWW.HALLMARKPANELS.COM 01482 781 111 ENQUIRIES@HALLMARKPANELS.COM

What Is Dual-Certification?

This means that the fire doors not only meet the strict fire safety requirements but also enhanced PAS24:2016 security standards (SBD Secured By Design).

This means that not only are our doors tested, but are externally audited to inspect that they are consistently manufactured correctly. Regularly taking doors from production and testing them to ensure they still meet the standards required.



G

Following extensive market research it was established that a viable alternative to Hardwood and PVCu outer frames was required for FD30 & FD60 doors that could reduce material costs, simplify production and reduce labour costs. Designed by Winkhaus UK, FireFrame® fulfils this criteria and ideally suits the Winkhaus AV2 multipoint locking system which is widely specified. Also includes the optional blueMatic AV2-E



Test Evidence

Tested up to 885 degrees celcius, withstanding fire exposure to both sides to achieve a 'pass' result, exceeding the requirement of 30 minutes performance. The image shows the test results at 30 minutes & 8 seconds show the doors successfully meeting the minimum target. Lasting up to the 39-minute point.



Hallmark solid & glazed FD30 composite fire doors average a minimum of 54% over the 30 minute requirement.

Hallmark FD30Sa Fire Door

Accreditation Requirement	30 Minutes
---------------------------	------------



Key benefits of a Hallmark FD30 composite fire door



MHCLG Approved

This door conforms to the Ministry of Housing, Communities & Local Government recommendation.



Fire & Smoke Tested

BS EN 1634 for fire resistance and smoke control.

3rd Party Accreditation

Fire and Security, 0 Mark 3rd Party independent factory audits ensure consistency of manufacture and specification.



Weather

Weather tested as part of the PAS24:2016 certification.



Performance

Door burn test to both sides in all 3 sizes of the NanYa slab in minimum & maximum sizes. To give you peace of mind that doorset has been fire tested to perform in all variations of size.



Security

PAS24:2016 (latest edition) enhanced security performance to resist methods of attack.



Toplight Options

Fire Doors are available with integral top lights and separate top light options.

Side lights coming soon.

Impressive dimension range

Available in the following sizes: Min Width 810mm inc Frame Max Width 1082mm inc Frame & add ons Min Height 2077mm inc Frame Max Height 2742mm inc Frame, add ons & top light



ENQUIRIES@HALLMARKPANELS.COM | WWW.HALLMARKPANELS.COM